

# ATENAS

## Millenium Series



## TECHNICAL SPECIFICATIONS

**Dimensions:** 52 - 54 cm seat centres  
55 cm depth  
95 cm height

**Backrest:** Cold moulded polyurethane foam 'UNIBLOCK 2' system, which wraps an injected polypropylene frame completely. All this structure is protected by a texturized injected polypropylene seat shell.  
Polyurethane density 55 Kg/m<sup>3</sup>

**Seat:** Cold moulded polyurethane foam 'UNIBLOCK 2' system, which wraps an injected polypropylene frame completely. All this structure is protected by a texturized injected polypropylene seat shell.  
The seat pan folds by means of an automatic noiseless maintenance-free double spring.  
Polyurethane density 65 Kg/m<sup>3</sup>

**Side panel:** Texturized injected polypropylene, 40mm  
End row panels completely upholstered  
Concealed floor fixation system

**Armrest:** Rounded texturized injected polypropylene.


**Volume:** 0.13 m<sup>3</sup> / unit

**Weight:** 15.80 Kg not assembled


# ATENAS

## Millenium Series

### DIMENSIONS AND DRAWING



### OPTIONS



### CERTIFICATES

- BS 5852:2006
- BS-EN 1021-1:2006
- CAL TB 117-2013, SECTION 1
- UNE 23.727-90 1R (M1)
- UNE-EN 1021-1:2006 / UNE-EN 1021-2:2006
- BS 5852:1979 Parte 1

Fabric	Fire Barrier	Foam
●		
●		
●		
●	●	
●	●	●
	●	



 [www.venueseating.dk](http://www.venueseating.dk)

 [info@venueseating.dk](mailto:info@venueseating.dk)

 + 45 70236923



Venue Seating ApS  
Lykkesholms Alle 7 B, 3 sal  
1902 Frederiksberg C  
Showroom: Smedeholm 11, 2730 Herlev