

### TECHNICAL SPECIFICATIONS



**Dimensions:** 54 a 56 cm seat centres  
63.5 cm depth  
96 cm height

**Backrest:** Cold moulded polyurethane foam 'UNIBLOCK 2' system, which wraps an injected polypropylene frame completely. It is later upholstered by means of a fabric cover and everything is protected by a varnished solid wood cover. Polyurethane density 55 Kg/m<sup>3</sup>

**Seat:** Cold moulded polyurethane foam 'UNIBLOCK 2' system, which wraps an injected polypropylene frame completely. It is later upholstered by means of a fabric cover. The seat pan folds by means of an automatic noiseless maintenance-free double spring. Polyurethane density 65 Kg/m<sup>3</sup>

**Side Panel:** Wood fibres board, finish in beech and a steel plinth. Concelaed floor fixation system.

**Armrest:** Included in the very side panel.

**Volume:** 0.120 m<sup>3</sup> / unit


**Weight:** 23.65 Kg not assembled




# LOGROÑO

## Studio Series

### DRAWING



### OPTIONS




### CERTIFICATES

BS 5852:2006  
 BS-EN 1021-1:2006  
 CAL TB 117-2013, SECTION 1  
 UNE 23.727-90 1R (M1)  
 UNE-EN 1021-1:2006 / UNE-EN 1021-2:2006  
 BS 5852:1979 Parte 1

| Fabric | Fire barrier | Foam | Seat |
|--------|--------------|------|------|
| ●      |              |      |      |
| ●      |              |      |      |
| ●      |              |      |      |
| ●      | ●            |      |      |
| ●      | ●            | ●    | ●    |
|        | ●            |      |      |



 [www.venueseating.dk](http://www.venueseating.dk)

 [info@venueseating.dk](mailto:info@venueseating.dk)

 + 45 70236923



Venue Seating ApS  
Lykkesholms Alle 7 B, 3 sal  
1902 Frederiksberg C  
Showroom: Smedeholm 11, 2730 Herlev